

## TR 315

|                  |                                     |
|------------------|-------------------------------------|
| <b>TYRE SIZE</b> | <b>23X8.50 -12</b>                  |
| <b>UM</b>        | IS STANDARD                         |
| <b>MACHINERY</b> | IMPLEMENT MACHINERY /<br>IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                            |
| <b>TL/TT</b>     | TL                                  |



### DIMENSIONS IS STANDARD

|                 |      |                         |                                      |
|-----------------|------|-------------------------|--------------------------------------|
| <b>SW (MM)</b>  | 205  | <b>RIM REC</b>          | 7 JA ; 7.00 I - 55 ; I - 70 ; I - 90 |
| <b>OD (MM)</b>  | 575  | <b>ECE</b>              | E4-106R-002178                       |
| <b>SLR (MM)</b> | 258  | <b>PR</b>               | 6                                    |
| <b>RC (MM)</b>  | 1668 | <b>TREAD DEPTH (MM)</b> | 12,5                                 |

### LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.30</b> |
| 15                | 650         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.