

# RIDEMAX IT 696

|                  |                        |
|------------------|------------------------|
| <b>TIRE SIZE</b> | <b>440/80 R 28 IND</b> |
| <b>UM</b>        | IS STANDARD            |
| <b>MACHINERY</b> | TRACTOR                |
| <b>VERSION</b>   | STANDARD               |
| <b>TL/TT</b>     | TL                     |
| <b>LI/SS</b>     | 156 A8 ; 151 D         |



## DIMENSIONS IS STANDARD

|                 |        |                         |                |
|-----------------|--------|-------------------------|----------------|
| <b>OD (MM)</b>  | 1415   | <b>RIM ALT</b>          | W 15 L         |
| <b>SLR (MM)</b> | 634    | <b>ECE</b>              | E4-106R-002299 |
| <b>RC (MM)</b>  | 4288   | <b>SRI</b>              | 675            |
| <b>RIM REC</b>  | W 14 L | <b>TREAD DEPTH (MM)</b> | 26,5           |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  |
|------------|------|------|------|------|------|------|
| 65         | 1620 | 2000 | 2345 | 2725 | 3070 | 3450 |
| 50         | 1765 | 2180 | 2555 | 2970 | 3345 | 3760 |
| 40         | 1880 | 2320 | 2720 | 3160 | 3560 | 4000 |
| 30         | 1955 | 2415 | 2830 | 3285 | 3700 | 4160 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.