

# RIDEMAX IT 696

|                  |                        |
|------------------|------------------------|
| <b>TIRE SIZE</b> | <b>400/80 R 24 IND</b> |
| <b>UM</b>        | IS STANDARD            |
| <b>MACHINERY</b> | TRACTOR                |
| <b>VERSION</b>   | STANDARD               |
| <b>TL/TT</b>     | TL                     |
| <b>LI/SS</b>     | 149 A8 ; 144 D         |



## DIMENSIONS IS STANDARD

|                 |       |                         |                |
|-----------------|-------|-------------------------|----------------|
| <b>OD (MM)</b>  | 1250  | <b>RIM ALT</b>          | W 12 ; W 14 L  |
| <b>SLR (MM)</b> | 558   | <b>ECE</b>              | E4-106R-002400 |
| <b>RC (MM)</b>  | 3760  | <b>SRI</b>              | 600            |
| <b>RIM REC</b>  | DW 13 | <b>TREAD DEPTH (MM)</b> | 26,5           |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  |
|------------|------|------|------|------|------|------|
| 65         | 1315 | 1625 | 1905 | 2210 | 2490 | 2800 |
| 50         | 1440 | 1775 | 2080 | 2415 | 2725 | 3060 |
| 40         | 1530 | 1885 | 2210 | 2570 | 2895 | 3250 |
| 30         | 1590 | 1960 | 2300 | 2670 | 3010 | 3380 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.