

## AS 504

|                           |                                                                                        |
|---------------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>          | <b>7.50 - 16</b>                                                                       |
| <b>UM</b>                 | IS STANDARD                                                                            |
| <b>CONSTRUCTION</b>       |  BIAS |
| <b>MACHINERY</b>          | IMPLEMENTS / TELEHANDLER / FIELD TRAILER / TELEHANDLER                                 |
| <b>VERSION</b>            | STANDARD                                                                               |
| <b>TL/TT</b>              | TT                                                                                     |
| <b>LI/SS DRIVE WHEEL</b>  | 99 A8                                                                                  |
| <b>LI/SS FREE ROLLING</b> | 112 A8                                                                                 |



### DIMENSIONS IS STANDARD

|                 |      |                |                                                |
|-----------------|------|----------------|------------------------------------------------|
| <b>SW (MM)</b>  | 209  | <b>RIM REC</b> | 5.50 F                                         |
| <b>OD (MM)</b>  | 803  | <b>RIM ALT</b> | 4.50 E ; 5.00 F ; 4.00 E ; 5 K ; 6 LB ; 6.00 F |
| <b>SLR (MM)</b> | 372  | <b>ECE</b>     | E4-106R-002633                                 |
| <b>RC (MM)</b>  | 2475 | <b>PR</b>      | 8                                              |

### LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.20 |
|------------|------|
| 10 FR      | 1570 |
| 25 FR      | 1335 |
| 30 FR      | 1255 |
| 40 FR      | 1120 |
| 10 DW      | 1085 |
| 25 DW      | 920  |
| 30 DW      | 870  |
| 40 DW      | 775  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.